


LASERENCORE

Professional laser light shows, displays and installations



STINGER RGB 18,000

Overview

STINGER RGB 18,000 is a full-color professional laser projector designed for medium to large-scale indoor and outdoor applications. Its high-powered output makes it a great choice for lighting designers and event professionals.



Specifications

Light Source

Red: 4440mW @ 637nm Single Mode Direct-Inject diodes

Green: 6000mW @ 520nm Multi-Mode Direct-Inject diodes

Blue: 8000mW @ 445nm Multi-Mode Direct-Inject diodes

Total Output @ Projector window: 14500mW ~ 15200mW

Beam Diameter (Projector Window): < 6 mm

Divergence (Full angle): < 0.9mrad (Full angle)

Modulation: Analog 50KHZ

Laser Class: Class IV

Scanner

Galvos: 35K (EMS 8000 40K upon request)


Scan Angle: 60° Max

Laser Encore Inc.

1-(651)633-8000 info@laserencore.com www.laserencore.com

LASERENCORE

Professional laser light shows, displays and installations



Interfaces & Controls

Control: ILDA in (Differential), ILDA out
Built-in Controller Pangolin FB4 (upon request)
DMX / Ethernet (Optional)
DMX in / Out (When FB4 & DMX daughter board is embedded)
Ethernet RJ45 in/Out (When FB4 is embedded)
Safety: Key Switch, Scan-Fail-Safe Switch
Remote Interlock: 5 pins XLR
Scan Image Invert: Invert – X, Invert – Y
Color adjustment: Intensity R, G, B (0-100%)
Mains: Neutrik PowerCon®

Thermal Control


Cooling: TEC Peltier Elements
Ventilation: 60mm Low noise fan * 4

Electric

Operating Voltage: AC 110V-240V
Power Consumption: 650W Max

Physical

L * W * H: 394mm * 282mm * 199mm (Without Yoke, Without feet)
Weight: 26 kg
Housing Materials: Black Anodized Aluminum
IP grade: IP54
Packaging: Flight case
CDRH, FDA, CE and RoHS certified



Laser Encore Inc.

1-(651)633-8000 info@laserencore.com www.laserencore.com